

Q-267R2

SVE BULLETIN

SPECIAL VEHICLE ENGINEERING – BODY BUILDERS ADVISORY SERVICE

E-Mail via Website: www.fleet.ford.com/truckbbas (click "Contact Us")

Toll-free: (877) 840-4338

QVM Bulletin: Q-267R1

Date: 05 September, 2017

Revised: 13 February, 2020

2017 and later F-Series Super Duty Chassis Cab 6.7L Diesel DEF Tank Relocation from Between Frame Rails to Outboard Location

Revision	Update	Revision Date
Q-267R1	<ul style="list-style-type: none"> Corrected part numbers 	23 October, 2017
Q-267R2	<ul style="list-style-type: none"> Added part number for 2020 model year 	13 February, 2020

Models Affected: 2017 and later F-Series Super Duty Chassis with 6.7L diesel engine and Aft-of Axle Fuel Tank Only.

Description: This Bulletin is intended to advise key service part numbers required to relocate the model year 2017 and later Super Duty Chassis Cab DEF tank from the inboard location (between the frame rails) to the outboard location (outside passenger side frame rail).

The inboard and outboard DEF tank locations have different mounting hardware. Additionally, an extended wire harness jumper and extended heated DEF line have been released to facilitate tank relocation. The following tables contain both the service part numbers of the standard inboard position mounting hardware and the service parts required for an upfitter to relocate the DEF tank from the inboard to outboard position.

Vehicles equipped with the DEF tank mounted in the standard, inboard position will have the following hardware installed from factory:

Inboard DEF Tank Mounting Hardware		
Service Part Number	Description	Quantity
HC3Z-5J231-A	STRP TNK EXH A/TRTMT SOLU MTNG (note: retain for use with outboard position)	2
HC3Z-5L212-C	BRKT ASY TNK EXH A/TRTMT SOLU	1
HC3Z-5L212-D	BRKT ASY TNK EXH A/TRTMT SOLU	1

The following service components are required for relocating the DEF Tank from the inboard location to the outboard location. They may be ordered through a Ford dealer:

Outboard DEF Tank Mounting Hardware		
Service Part Number	Description	Quantity
HC3Z-5L212-A	BRKT ASY TNK EXH A/TRTMT SOLU	1
HC3Z-5L212-B	BRKT ASY TNK EXH A/TRTMT SOLU	1
HC3Z-5C106-A	PLT ASY FR TO BDY SUPT	1
HC3Z-14A655-A	Electrical Jumper Harness* 2017 through 2019	1
LC3Z-14A655-A	Electrical Jumper Harness* 2020 and later	1
HC3Z-5J249-T	Extended DEF line*	1
*Required parts specific to tank relocation		

Note:

The inside left

frame rail (mid-ship) position is the factory default position with aft-of-axle fuel tank. If the

mid-ship fuel tank or mid-ship and aft-of-axle tanks are ordered, the urea tank will be packaged on the outside right frame rail. There is no recommended tested position to relocate the urea tank when the mid-ship fuel tank is ordered.

Refer to the workshop manual for tank removal and installation procedure.

Additional guidelines:

After any modification on or near the urea supply line, inspect the entire length of the line from the urea tank to the exhaust injector. Look for areas that may have been impacted by jacking, hoisting, cutting, welding or repositioning of components.

Verify that all (6) connectors related to the urea tank and fluid supply line are fully seated by using a push/click/pull method.

Start vehicle and allow it to run for a minimum of 10 minutes. Inspect for any leaks. Check the instrument cluster for warning lights or messages related to the Diesel Exhaust Fluid System. If extensive troubleshooting is required, please contact your local authorized Ford Service Center.